

REPORT OF ANALYSIS

Multi-Element Aqueous RM

SM68 Standard 3

Product #: LK1-CB724538C-100

Matrix: 10% HCI

Lot #: 1029788-27

Indicative Value(s) Density: 0.988 g/mL @ 20°C

Element	Certified Concentration	Element	Certified Concentration	Element	Certified Concentration	
Au	100.0 μg/mL	Pd	100.0 µg/mL	Ru	100.0 µg/mL	
lr	100.0 µg/mL	Pt	100.0 µg/mL	Те	99.99 µg/mL	
Os	100.0 µg/mL	Rh	100.0 µg/mL			

Intended Use: This solution is intended for use as a reference material (RM) or calibration standard for inductively coupled plasma optical emission spectroscopy (ICP-OES), inductively coupled plasma mass spectrometry (ICP-MS), flame or furnace atomic absorption spectroscopy (AA or GFAA), and other techniques for elemental analysis.

Certification & Traceability: This RM was manufactured, processed, and/or certified under a quality management system that is registered/accredited to 9001 (TUV NORD Certificate No. 44 100 16560231), ISO 17034, and ISO/IEC 17025 (certificate number 2848.01) by the American Association of Laboratory Accreditation (A2LA). This RM was prepared to the certified concentrations shown above by gravimetric methods using single-element concentrates, and was stabilized using high purity hydrochloric acid (HCI) and diluted with filtered (0.22 μ m), 18 M-ohm deionized water. The balances used in the preparation of this RM are calibrated regularly with traceability to NIST, using a calibration provider that is accredited to ISO/IEC 17025 by a mutually recognized accreditation body. All volumetric dilutions are performed in Class A calibrated glassware. The certified concentrations were determined based upon gravimetric procedures. Secondary verification of the certified concentrations was performed using ICP-OES that was calibrated and/or referenced against NIST SRMs (see reverse side). The uncertainty associated with the certified concentration is ±0.5% relative, which is the sum of the estimated errors due to the purity of the raw materials, the gravimetric preparation of the solution, and transpiration through the container. This represents the expanded uncertainty at the 95% confidence level using a coverage factor of k=2.

Instructions for Use: We recommend that the solution be thoroughly mixed by repeated shaking or swirling of the bottle immediately prior to use. To achieve the highest accuracy, the analyst should: (1) use only pre-cleaned containers and transferware, (2) not pipette directly from the RM's original container, (3) never pour used product back into the original container, (4) make dilutions using calibrated balances or certified class A volumetric flasks and pipettes, (5) use a minimum sub-sample size of 500 µL, and (6) dilute with the same matrix as the original RM or other chemically suitable matrix. The solution should be kept tightly capped and stored under normal laboratory conditions. Do not freeze, heat, or immerse the bottle or its contents, and avoid exposure to direct sunlight or moisture.

Period of Validity: LabKings ensures the accuracy of this solution for 12 months from the certification date shown below, provided the instructions for use are followed. During the period of validity, the purchaser will be notified if this product is recalled due to any significant changes in the stability of the solution.

December 4, 2020

Chuck Goudreau, Certifying Officer LabKings waives all responsibility for any damages resulting from the usage and/or implementation of the products/data described herein.

Crown your labwork

This CRM is traceable to the following NIST SRMs:

Analyte	Aq. SRM	MO SRM	Analyte	Aq. SRM	MO SRM		Analyte	Aq. SRM	MO SRM
Ag	3151	-	Hf	3122	-		S	3154	2770
AI	3101a	-	Hg	3133	3133		Sb	3102a	3102a
As	3103a	3103a	Ho	3123a	-		Sc	3148a	3148a
Au	3121	-	In	3124a	3124a		Se	3149	3149
В	3107	3107	К	3141a	3141a		Si	3150	-
Ва	3104a	-	La	3127a	3127a	1	Sm	3147a	-
Be	3105a	3105a	Li	3129a	3129a		Sn	3161a	-
Bi	3106	3106	Lu	3130a	-		SO4-2	3181	-
Br-	3184	-	Mg	3131a	3131a		Sr	3153a	3153a
Ca	3109a	3109a	Mn	3132	3132		Та	3155	-
Cd	3108	-	Мо	3134	3134		Tb	3157a	-
Ce	3110	3110	Na	3152a	-	1	Te	3156	-
Cl-	3182	1818a	Nb	3137	-	1	Th	-	-
Co	3113	3113	Nd	3135a	-		Ti	3162a	3162a
Cr	3112a	-	Ni	3136	-		TI	3158	3158
Cs	3111a	-	NO ₃₋	3185	-		Tm	3160a	-
Cu	3114	-	Р	3139a	3139a		U	3164	-
Dy	3115a	-	Pb	3128	-	1	V	3165	-
Er	3116a	-	Pd	3138	-		W	3163	3163
Eu	3117a	-	PO ₄ -3	3186	-		Y	3167a	3167a
F-	3183	-	Pr	3142a	-	1	Yb	3166a	-
Fe	3126a	-	Pt	3140	3140		Zn	3168a	3168a
Ga	3119a	-	Rb	3145a	-]	Zr	3169	3169
Gd	3118a	-	Re	3143	-				
Ge	3120a	-	Rh	3144	3144				