

Page 1/11

Tel: +31 35 240 0142

Web: www.labkings.com

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3
- · Part number: LK1-00040101
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Reference material for laboratory use only
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

LabKings B.V. Hoge Naarderweg 42, 1217 AG Hilversum The Netherlands

- $\cdot \textit{Further information obtainable from: } info@labkings.com$
- 1.4 Emergency telephone number: +31 35 240 0142

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Carc. 1B H350i May cause cancer by inhalation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Page 2/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 1)

· Hazard pictograms







GHS05 GHS07 G

- · Signal word Danger
- · Hazard-determining components of labelling:

Nitric acid

Beryllium Oxyacetate

· Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H350i May cause cancer by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Aqueous solution.

(Contd. on page 3)



Page 3/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from pa				
· Dangerous components:				
CAS: 7697-37-2	Nitric acid	<5%		
EINECS: 231-714-2	🕸 Ox. Liq. 2, H272; 📀 Met. Corr.1, H290; Skin Corr. 1A, H314			
RTECS: QU5775000				
CAS: 19049-40-2	Beryllium Oxyacetate	<2%		
EINECS: 242-785-4	Acute Tox. 3, H301; Acute Tox. 2, H330; & Carc. 1B, H350i; STOT RE 1,			
RTECS: DS2900000	Acute Tox. 3, H301; Acute Tox. 2, H330; & Carc. 1B, H350i; STOT RE 1, H372; & Aquatic Chronic 2, H411; & Skin Irrit. 2, H315; Eye Irrit. 2, H319;			
	Skin Sens. 1, H317; STOT SE 3, H335			
Additional information	on: For the wording of the listed hazard phrases refer to section 16.			

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur even after several hours; therefore medical observation for at least 48 hours after the accident is recommended.

· After inhalation:

Supply fresh air and call a doctor.

In case of unconsciousness place patient in recovery position for transport.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Rinse mouth. Do not induce vomiting.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

NLEN



Page 4/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

DO NOT USE SAWDUST.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/extraction at the workplace.

Store in cool, dry place in tightly closed receptacles.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Please refer to the manufacturer's certificate for specific storage and transport temperature conditions.

Store only in the original receptacle unless other advice is given on the CoA.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)



Page 5/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 4)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 7697-37-2 Nitric acid

WGW (Netherland) Short-term value: 1.3 mg/m³, 0.5 ppm

- · Additional information: Lists used were valid at the time of SDS preparation.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374



Protective gloves

· Material of gloves

PVC gloves

Neoprene gloves

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

NII EN



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L \pm 0.3% (Be Acetate), 4% HNO3

(Contd. from page 5)

SECTION 9: Physical and chemical properties			
9.1 Information on basic physical and	d chemical properties		
General Information			
Appearance:			
Form:	Liquid		
Colour:	Colourless		
Odour:	Odourless		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/freezing point:	Not determined.		
	Not determined.		
Initial boiling point and boiling range: $100~^{\circ}C$			
Flash point:	Not applicable.		
Flammability (solid, gas):	Not determined.		
Ignition temperature:	Not determined		
Decomposition temperature:	Not determined.		
Auto-ignition temperature:	Product is not selfigniting.		
Explosive properties:	Not determined.		
Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
Vapour pressure at 20 °C:	23 hPa		
Density:	Not determined.		
Relative density	Not determined.		
Vapour density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
water:	Fully miscible.		
Partition coefficient: n-octanol/water	: Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
9.2 Other information	No further relevant information available.		



Page 7/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 6)

SECTION 10: Stability and reactivity

· 10.1 Reactivity

Stable under normal conditions.

No further relevant information available.

- · 10.2 Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

Formation of toxic gases is possible during heating or in case of fire.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Heat.
- · 10.5 Incompatible materials:

Strong oxidizing agents.

Metals.

· 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 7697-37-2 Nitric acid

Inhalative LC50/4 h 130 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carc. 1B

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

May cause cancer by inhalation.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

NLEN



Page 8/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 7)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 7697-37-2 Nitric acid

LC50/48 180 mg/l (crustacean)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

Waste disposal key numbers from EWC have to be assigned depending on origin and processing.

- · Uncleaned packaging:
- · Recommendation: Dispose of in accordance with national regulations.
- $\cdot \textit{Recommended cleansing agents:} \ \textit{Water, if necessary together with cleansing agents.}$

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

 $\cdot ADR$

3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

· IMDG, IATA CORROSIVE LIQU

 $CORROSIVE\ LIQUID,\ ACIDIC,\ INORGANIC,\ N.O.S.$

 $(NITRIC\ ACID)$

(Contd. on page 9)



Page 9/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 8)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Danger code (Kemler):	80
· EMS Number:	F- A , S - B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Annex Marpol and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport eategory	Maximum net quantity per outer packaging: 1000 ml 3
· Transport category · Tunnel restriction code	S E
· UN ''Model Regulation'':	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 9)

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise when using, handling and/or storing the material. The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. Labkings makes no warranties or representations as to the accuracy and completeness of the information contained herein, shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.

· Relevant phrases

H272 May intensify fire; oxidiser.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H350i May cause cancer by inhalation.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Ox. Liq. 2: Oxidizing liquids - Category 2

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 11)



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.05.2020 Version number 1 Revision: 01.05.2020

Product name: Beryllium 10,000 mg/L ± 0.3% (Be Acetate), 4% HNO3

(Contd. from page 10)

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Carc. 1B: Carcinogenicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

 $STOT\ RE\ 2:\ Specific\ target\ organ\ toxicity\ (repeated\ exposure)-Category\ 2$

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

· Data compared to the previous version altered. All sections have been updated.

NLEN